

CHAIN HOISTS



Chain is available in various lengths.

INDUSTRIAL RANGE: SPECIFICATIONS & DIMENSIONS

MODEL NO.			6GCB0.5	6GCB1	6GCB1.6	6GCB2	6GCB3.2	6GCB5	6GCB10	6GCB15	6GCB20
Capacity		(ton)	0.5	1	1.6	2	3.2	5	10	15	20
No. of Falls			1	1	1	1	2	2	4	6	8
Capacity Test Load		(ton)	0.75	1.5	2.4	3	4.8	7.5	15	22.5	30
Load Chain		(mm)	5 × 15	6 × 18	8 × 24			10 x 30			
Load Chain Grade			80								
Standard Lift		(m)	3	3	3	3	3	3	3	3	3
Hand Chain		(mm)	5 × 25 × 17								
Height	H	(mm)	290	330	375	405	490	630	815	1 000	1 300
Length	A	(mm)	8.0	11.3	15.8	17.3	23.2	40.2	67.5	121.2	150.6
Width	B	(mm)	8.4	11.7	16.3	17.9	23.7	41.2	76.5	134.1	160.6
Net Weight		(kg)	8.3	11.5	14.6	17.6	21.7	44.7	71.7	139.4	156.7
Gross Weight		(kg)	8.7	12.1	15.1	18.4	22.4	49.4	80.7	152.5	170.5
Pull to Rated Load		(N)	219	254	351	405	366	385	426	447	440 x 2
Dimensions	A	(mm)	130.0	155.0	173.0	185.0	235.0	262.0	365.0	406.0	550.0
	B	(mm)	127.0	134.0	151.0	157.0	157.0	180.0	180.0	210.0	225.0
	C	(mm)	135.5	160.5	179.0	189.0	179.0	233.0	233.0	233.0	233.0
	D	(mm)	35.0	45.0	47.0	52.0	62.5	79.0	-	-	-
	E	(mm)	27.0	32.7	33.5	37.0	43.5	51.0	64.0	80.0	82.0
	F	(mm)	16.8	21.4	25.4	28.8	36.1	44.0	60.2	85.6	85.6
	G	(mm)	12.0	16.5	18.8	21.0	29.0	32.0	42.0	56.1	56.1
	H	(mm)	290	330	375	405	490	630	815	1 000	1 300